

# MD116 Accessory Selection

## Vehicle Dock OPM-T016-A3



### Specifications

Description	Vehicle Dock
Input Power	12V
Installations	VESA 75
IO	2x USB 2.0 Type-A 1x RJ45 1x Line Out 1x Phoenix Port 1x DC In Jack
LED Indicator	N/A
Dimensions	236.89 x 293.03 x 88.22mm
Weight	800g
Operating Temperature	0°C ~ 40°C(32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)

### Optional Accessories

- OPM-T016-A3  
MD116 Vehicle Docking Plus . USB x2 /LAN / Line out

## Office Dock OPM-T022-A1



### Specifications

Part Number	OPM-T022-A1
Description	Office Dock
Input Power	12V
Installations	Stationary
IO	2x USB 2.0 Type-A 1x RJ45 1x RS-232 1x DC-In Video out (optional) 1x HDMI , 1x DP
LED Indicator	Steady Green: Connection LED Off: Disconnection
Dimensions	354 x 117 x 78.2mm
Weight	1060g
Operating Temperature	0°C ~ 35°C(32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)

### Optional Accessories

- OPM-T022-A1  
MD116 Office Dock
- OPM-T022-A2  
MD116 office Dock HDMI
- OPM-T022-A3  
MD116 office Dock DP

Mobile Medical Tablet

# MD116 Accessory Selection

## VESA Cradle

OPM-T021-A1



## Specifications

Description	VESA Cradle
Input Power	N/A
Installations	VESA 75
IO	N/A
LED Indicator	N/A
Dimensions	206.69 x 196.64 x 87.8mm
Weight	395g
Operating Temperature	0°C ~ 40°C(32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)

## Optional Accessories

- OPM-T021-A1  
MD116 VESA Cradle

# MD116 Accessory Selection

## Battery Pack x2

OPM-P05T



### Specifications

Battery Type	253P / 6 Cell Lithium-ion battery
Battery Voltage	7.2V
Battery Capacity	4545 mAh / 32.72Wh
Warranty	1 year
Certification	UL,CE,IEC-60950-1,IEC-62133-1

#### MECHANICAL AND ENVIRONMENTAL

Color	Black
Dimension	127(L) x 60(w) x 21(H) mm
Net Packing Size	199(L) x 175(w) x 42(H) mm
Weight	305g/pcs
Gross Weight	0.9kg(1.98 lbs)
Operating Temperature	0°C ~ 40°C(32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)

### Ordering Information

- OPM-P05T-A2  
2 Battery Kits.2S3P.7.2V.Onyx MD116.Volume Package

## Battery Charger

UP-M62



### Specifications

Description	Battery Charger
Input Power	24V
Installations	Stationary
IO	1x Micro USB (Client) 1x DC-In
LED Indicator	Flickering Blue: Battery Charging Steady Blue: Battery Fully Charged Flickering Purple Green: Error
Dimensions	245.95 x 124.64 x 143.65mm
Weight	860g
Operating Temperature	0°C ~ 35°C(32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)

### Optional Accessories

- UP-M62-A1-1010  
MD116 6-slots Charger

# MD116 Accessory Selection

## Desk Stand

OPM-H26S



## Specifications

Description	Desk Stand
Color	Black
Installations	MD116 / MD116i Screw hole
IO	N/A
Dimensions	250x 153 x 126.2 mm
Weight	500g
Minimum Package Size	610 x 240 x 330 mm (Incl.5pcs)
Minimum Package Weight	3 kg (Incl.5pcs)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)

## Optional Accessories

- OPM-H26S-A1  
MD116 Desk Stand